



Standard Battery Charger RRC-SMB-UBC for Smart Batteries

Features:

- 65W Single bay fast charger
- For the standard battery pack form factors RRC2020, 2024, 2040, 2040-2, 2054, 2054-2, 2057 or smart batteries with a similar footprint (e.g. 202x range, 204x range, 205x range, DR36, etc.)
- Optimized charging process for RRC batteries
 - Longer cycle life
 - Faster charging
- Simple operation – Plug and Play
- Automatic recognition and calibration of smart battery learned capacity
- External power supply for worldwide use
- Country specific AC input cables available

Applications:

Standard charging station for mobile devices used in medical, industrial and consumer markets

Specification RRC-SMB-UBC

Input		Output	
Voltage range	19 - 26VDC	Voltage range	0 - 17.4VDC
Current	3400mA max.	Current range	0 - 4.8A
Power	65W	Voltage tolerance	±1% max.
		Current tolerance	±10% max. @1A, ±3% max. @4A
		Protection	Short circuit Over temperature shutdown Input-/output over current

Environmental		General	
Cooling	convection cooled	Efficiency	~95% at 100% load
Temperature	Operating: 0°C to 40°C Non-operating -10°C to 70°C	Indicator	Multi-color LED (green, red, orange)
Pressure & Altitude	Operating: 1060hPa to 795hPa -382m to 2000m Non-operating: 1060hPa to 572hPa -382m to 4570m	Battery types	Standard battery form factors RRC2020, 2024, 2040, 2040-2, 2054, 2057 or smart batteries with a similar footprint (e.g. 202x range, 204x range, 205x range, DR36, etc.)
Humidity	5% to 95% r.H., non-condensing	Green procurement	RoHS 2011/65/EU WEEE 2012/19/EU Chinese RoHS

LED Indications	
One time Red/Orange/Green	Selftest: Charger is ready for use.
Red/Green blinking	Battery recognition and initialization.
Orange blinking	The battery is currently being calibrated.
Orange light	The inserted battery is of the correct type and is currently being charged.
Green light	The battery is charged and can be removed for use.
Red blinking	The battery is too hot or too cold to be charged without damage. If the battery is too cold it will be charged as soon as it has warmed up sufficiently. If the battery is too hot it should be removed to cool down.
Red light	The battery is damaged or it is a conventional battery which cannot be recharged.

Charger Mechanical Details	
Housing dimensions (LxWxH)	151 x 90 x 43mm
Weight	198g (excluding power supply)

Safety & EMC		
	In combination with included external AC/DC power supply	
Regulatory approvals	Europe	CE
Electromagnetic Emissions	Europe	EN55011, EN55022, level B
Electromagnetic Immunity	USA	FCC15 class B
	ESD immunity	EN/IEC61000-4-2
	Electromagnetic field immunity	EN/IEC61000-4-3
	EFT / Burst	EN/IEC61000-4-4
	Surge	EN/IEC61000-4-5
	Conducted Immunity	EN/IEC61000-4-6
	Magnetic Fields	EN/IEC61000-4-8
	Voltage dips, short instrumentations & voltage variations	EN/IEC61000-4-11
	Immunity characteristics	EN55024

Specification external power supply AC/DC

Input		Output	
Voltage range	100 - 240VAC	Voltage range	19VDC
Current	1.7A max.	Power	65W max.
Stand by power	No load < 0.5W @ 230 VAC	Current range	3.4A
		Protection	Over voltage, over current, Short circuit

Environmental		General	
Temperature	Operating: 0°C to 40°C Non-operating -10°C to 70°C	Efficiency	California's Energy Efficiency Level VI
		Ripple & Noise	300mV (p-p)

Power Supply Mechanical Details	
Standard output connector	DC barrel jack
Housing dimensions (LxWxH)	95 x 51 x 25.4mm
Weight	270g

Safety & EMC & Approvals		
Approvals	Europe	CE
	International	CB
	USA/Canada	cULus
	Australia & New Zealand	RCM
	Russia (Customs Union)	EAC
	Korea	KC
	China	CCC
	Japan	PSE
	India	BIS

Germany/Headquarters USA

RRC power solutions GmbH
Technologiepark 1
D-66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

Emerging Power, Inc.
200 Holt Street
Hackensack, NJ 07601

Tel.: +1 201 441 3590
Fax: +1 201 441 3592
Email: vmiller@emergingpower.com
Web: www.emergingpower.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial Centre
2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 520, Yuanlin Building,
Aiguo Road No. 3066,
Luohu District,
Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com